

CBF

CRUSHER BUCKET













Crusher bucket designed for crushing inert material directly on site. Suitable for any type of construction site, it can work in the most difficult conditions while maintaining performance.

STRENGTHS

- Body built 90% in wear-resistant material
- Crushing plates made of a 18% manganese cast
- Single pressure relief valve and speed regulation

- Output size adjustment from 25 to 125 mm
- Easy and uncomplicated maintenance























OPTIONAL

- Magnet + Control panel kit
- Pre-arrangement for backhoe / wheel loader / telelescopic handler

| DATA SHEET | | CBF 05 | CBF 06 | CBF 07 | CBF 09 | CBF 12 |
|---------------|----------------|------------------------|------------------------|------------------------|-------------------------|-------------------------|
| Excavator | ton | ≥7 <10 | ≥10 <13 | ≥13 <20 | ≥20 <30 | ≥30 <45 |
| Mouth size | mm | 500 x 420 | 600 x 500 | 700 x 550 | 900 x 550 | 1200 x 550 |
| Weight | Kg | 1250 | 1630 | 2250 | 3500 | 5000 |
| Load capacity | m ³ | 0,43 | 0,58 | 0,70 | 0,85 | 1,00 |
| Pressure | bar | 200 | 200 | 200 | 200 | 200 |
| Oil flow | l/min | 120 | 130 | 150 | 180 | 220 |
| Opening | mm | 25/100 | 25/100 | 25/125 | 25/125 | 25/125 |
| Dimensions | wxdxH | 700 x 1700 x H 1200 | 800 x 1900 x H 1300 | 900 x 2100 x H 1450 | 1150 x 2100 x H 1600 | 1450 x 2100 x H 1600 |

CRUSHING SIZE FROM 25 UP TO 125/25 mm STEP.
Weights and dimensions could vary without notice. Weight does not include the coupler.

